

14GN / 14PH

TANDEM AXLE GOOSENECK

G.V.W.R. 14,000#	AXLES Two 7000# EZ LUBE w/ Elec. Brakes
G.A.W.R. (Ea. Axle) 7,000#	SUSPENSION Multi-Leaf Slipper Spring w/ Equalizer
COUPLER 2-5/16" Ball Adj. Pipe / 3" ID Firtle on FH	TIRE ST235/85 R16 Load Range E
SAFETY CHAINS 3/8" Grd. 70 w/Safety Latch Hook (2 ea.)	WHEEL 6.00 X 16" HD White Modular - 8 Bolt
JACK 12,000# Drop Leg Jack (Bolted On)	FLOOR 2" Pine
NECK 10" Channel	LOADS D.O.T. Stop, Tail, Turn and Clearance
TOP RAIL (none)	ELEC. PLUG 7-Way RV
FRAME 12" - 16# I-Beam	FINISH (EXTER) Acid Etched w/White Phosphorus, Undercoated w/Parther 813 & Two Coats Primer
CROSSMEMBERS 3" Channel	FINISH Painted w/2 Coats High Solid Supreme Acrylic Automotive Grade Enamel, and Pinstriped
SIDE RAILS 6" Channel w/ Rub Rail and	

- 5' Dovetail w/Double Hinged Spring Assist Fold-Over Ramps
- Complete Break-A-Way System w/ Battery & Charger
- Rubber Mounted Sealed Lighting
- Cambered Ez Lube Axles
- Modular Sealed Wiring Harness
- Safety Reflective Marker Tape

- (2) Side Bed Steps
- Spare Tire Mount
- 3/8" Heavy Duty Rub Rail
- 102" Overall Width
- Chain Basket between the gooseneck
- Firtle has Single TW Drop-Leg Jack
- Bolt On Jack w/ Greasable Handle
- Radial Tires on HD Wheels

- Floor Secured w/ 5/16" Torx Screws

DIMENSIONS - WITH DOVETAIL			
MODEL	A	B	C
20+5	240	19.6	44
22+5	264	21.4	48
24+5	288	23.2	52
26+5	312	24.9	56
28+5	336	26.6	60

14GN / 14PH



PRICING

MODEL #	WEIGHT	DESCRIPTION	PRICE
14GN-20+5	4825#	102' X 20' +5' Tandem 14,000# Gooseneck/Firtle (14PH)	
14GN-22+5	5085#	102' X 22' +5' Tandem 14,000# Gooseneck/Firtle (14PH)	
14GN-24+5	5440#	102' X 24' +5' Tandem 14,000# Gooseneck/Firtle (14PH)	
14GN-26+5	5795#	102' X 26' +5' Tandem 14,000# Gooseneck/Firtle (14PH)	
14GN-28+5	6155#	102' X 28' +5' Tandem 14,000# Gooseneck/Firtle (14PH)	

OPTIONS

No Dovetail (Straight Deck)	
5' Center Pop-Up Dovetail w/5' Fold-up Ramps	
Torsion Axles	
Square Adjustable Screw Type Coupler	
Dual Drop Leg Jacks (Single Speed)	
Single Two Speed Drop-Leg Jack	
Dual Two Speed Landing Gear Jacks (150K)	
Deck On The Neck (6')	
16" Spare Tire & Wheel	
16" Spare Tire & Wheel - Load Range F	
Tire Upgrade to LT235/85 R16 LR "F"	
Low Profile Tool Box 12" X 18" X 36" (Side Mount)	
Tool Box 18" X 18" X 36" (Side Mount)	
L.E.D. Lighting	
Elec/Hydr. Brakes (Drum)	